

FEATURES:

- Slim wall socket housing*
- MTBF – 50 000 h*
- Meets energy star level V*
- Widel AC input / full range*



SPECIFICATION:

output	Model	Voltage DC [V]	Current min [A]	Current max. [A]	Tolerance [%]	Efficiency [%]	Power max. [W]	Ripple & noise [mV]	DC plug
	Cellevia AC/DC-CL5/1.2A	5	0	1.2	+/- 5	>68.13	6	100	2.1x5.5
input	voltage	100 - 240V							
	voltage range	90 - 264V							
	frequency min. / max	47 - 63 Hz							
	frequency	60HZ / 50Hz							
	current	0.2 Amax @ 100 VAC							
	inrush current	50 Amax @ 264 VAC							
protection	OCP	Overload							
	OVP	Over voltage							
	SC	Short circuit							
	insulation	Class II							
	min. load requirement	No							
others	MTBF	50000h							
	efficiency [%]	>68.13							
	dimensions (LxWxH) / weight	40.3 x 38.6 x 65 mm / 81g (100pcs/cartoon)							
environmental	operating temp.	0 ~40 deg C							
	storage temp.	-20 ~85 deg C							
	relative humidity	10 ~90% RH							
	storage relative humidity	10% ~90% RH							
safety	CE	EN60950-1							
	TUV - GS	EN60950-1							
EMC	EMI	EN 55022:1998, +A1:2000 +A2:2003, CLASS B							
		CISPR 22:2003, CLASS B							
		AS/NZS CISPR22: 2004, CLASS B							
	EMS	EN 61000-3-2, EN 61000-3-3, EN 61000-4-2, EN 6100-4-3, EN 6100-4-4,EN61000-4-5, EN61000-4-6 EN 61000-4-8, EN 61000-4-11							