

Features:

- Protections: Short circuit/Overload/Over Voltage/Over Temperature
- IP protection standard: IP67
- Efficiency: 75%
- 100% full load burn-in test
- Storage temperature: -40-80°C
- Operating temperature: -25-45°C
- Certificate: CE, ROHS



SPECIFICATION: ZLV-200-12		
Input Voltage (VAC)		170-250VAC
Input Current		1.5Amax@220VAC
Input Frequency (Hz)		47 to 63 Hz
Output Voltage (VDC)		12VDC±0.5V
The sum output current(A)		16.7A
Max output Power (W)		200W
Short Circuit Protection		Auto recovery
Overload Protection		20% exceed is allowing
Over-voltage Protection		≤255V
Thermal Protection		≤80°C
Temperature rising		≤28°C
CE	CE Safety Standard	Compliance to EN61347-1:2001 / EN61347-2-11.2001
	EMI conduction & radiation	Compliance to EN55015,EN61547
	Harmonic Current	Compliance to EN61000-3-2,-3
Others	Dimension/Weight	228*125*65 MM/2.6kg
	Packing/Carton Size	5pcs/carton / 43*29.3*18.5cm
	Cable	0.75sq.mm. VDE wire 400mm
	Housing Material	Aluminum