

**Features:**

·Protections: Short circuit/Overload/Over Voltage/Over

Temperature

·IP protection standard: IP67

·Efficiency: 75%

·100% full load burn-in test

·Storage temperature: -40-80°C

·Operating temperature: -25-45°C

·Certificate: CE, ROHS



SPECIFICATION: ZLV-30-12		
Input Voltage (VAC)	170-250VAC	
Input Current	0.45Amax@220VAC	
Input Frequency (Hz)	47 to 63 Hz	
Output Voltage (VDC)	12VDC±0.5V	
The sum output current(A)	2.5A	
Max output Power (W)	30W	
Short Circuit Protection	Auto recovery	
Overload Protection	20% exceed is allowing	
Over-voltage Protection	≤255V	
Thermal Protection	≤80°C	
Temperature rising	≤28°C	
CE	CE Safety Standard	Compliance to EN61347-1:2001 / EN61347-2-11.2001
	EMI conduction & radiation	Compliance to EN55015,EN61547
	Harmonic Current	Compliance to EN61000-3-2,-3
Others	Dimension/Weight	200*30*20MM/260g
	Packing/Carton Size	50pcs/carton / 34*24*18cm
	Cable	0.75sq.mm. VDE wire 200mm
	Housing Material	Aluminum