

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® C182 - 7x0,25 mm²

Spiral Shielded Multi-Conductor Cable



CATEGORY Spiral Shielded Cables (See Audio Catalogue)
APPLICATIONS Sound Reproduction and Electronics.

- A:** Black Soft **PVC** Sheath. Outer Diam. Ø 6,30 (±0,20) mm.
- B:** O.F.C. red copper spiral Shielding, covering 100%.
- C:** Soft **PVC** Core Insulation with. Color Code: Red, Blue, Yellow, Brown, White, Grey, Black. Core Diam. Ø 1,50 (±0,10) mm.
- D:** O.F.C. Red Copper stranded formation 8x0,20 mm. Nom. Cross section 7x0,25 mm².

MARKING **tasker®** C182 7x0.25 Spiral Shielded Cable – Made in Italy
CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	75,85 Ω/Km
Capacity Core/Core	120 pF/mt
Capacity Core/Shield	210 pF/mt
Max Rated Voltage	49 V
Operative Temperature	-15/+70° C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Flexible Limited	Flessibilità limitata	Informazioni	X	Ver. A / 17.06.16
		Outdoor	Esterno			Dynamic (Drag Chain)	Mobile in Catena			
		Outdoor Direct Burial	Esterno Interrato			Dynamic (Torsion)	Mobile in Torsione			