

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it



## Technical Datasheet

### tasker® C256 - 3x0,22 mm<sup>2</sup> - Special Microphone Cable



**CATEGORY** Microphone Cable (See Audio Catalogue)  
**APPLICATIONS** Audio e Microphone premade cables

- A:** Black Soft **PVC** Sheath.  
Outer cable Diam. Ø 5,20 (±0,20) mm.
- B:** Braided Shielding in O.F.C. red copper covering 60% + textile waste filler between conductors and wrapped with not woven polyester based tape.
- C:** Cores Insulation with compact PE. Diam. Ø 1,20 (±0,20) mm.  
Color Code: White, Yellow, Red.
- D:** Conductors in O.F.C. red copper with stranded formation 7x0,20 mm.  
Nom. Cross section 3x0,22 mm<sup>2</sup>.

**MARKING** tasker® C256 3x0,22 mm<sup>2</sup> O.F.C. Shielded Audio Cable  
**CUSTOM** This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR,**  
**PRODUCTION** with or without Metallic Armor.

#### Cable Properties

<b>Conductor Resistance</b>	79,15 Ω/Km
<b>Capacity Core/Core</b>	66 pF/m
<b>Capacity Core/Shield</b>	113 pF/m
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			