



Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Contact Factory mjm@hammondmfg.com for quotes
Solid models of this enclosure available in STEP or IGES.

Purchased assembly includes box, lid and 4 cover screws.  Sox and lid are made from Diecast Aluminum Alloy (alloy type 3 silicone Gasket Loctite #5950	80).
PART NUMBERS	
1590V Enclosure	
Unfinished	1590V
Grey Textured Polyester Powder Paint - RAL 7038	1590VGY
Black Textured Polyester Powder Paint - RAL 9011	1590VBK
1590V Liquid Resistant Enclosure (Silicon Factory	
Unfinished	1590W V
Black Textured Powder Paint	1590W VBK
ACCESSORIES	
Recommended Torque: 75 ozf.in / 5	5 cN.m
Black Textured Cover Screws (Pkg 50) [6-32 x 1/2" SS Type 304]	1590WMS100BK
Unfinshed Cover Screws (Pkg 100) [6-32 x 1/2" Nickel Plated Screws]	1590WMS100
Standard Cover Screws	
Unfinshed Cover Screws (Pkg 100) [6-32 x 1/2" Nickel Plated Screws]	1590MS100
Black Textured Cover Screws (Pkg 50) [6-32 x 1/2" SS Type 304]	1590MS100BK

