KEMET Part Number: PMR209ME6470M100R30

(P409EL474M250AH101)



General Information

KEMET

Metallized Paper

Radial Molded

Wire Leads

Pulse

0.47 uF 630 VDC

+/-20%

85C

250 VAC

-40/+85C

(AltPart)

2.13 GOhm

Not For New Design, Please

Resistor= 100 Ohms

Check Possible Alternative Parts

Yes

Specifications

Integrated Resistor (X2)

Supplier:

Style:

Dielectric:

Application:

Lead Form:

Capacitance:

Voltage AC:

Rated Temperature:

Temperature Range:

Miscellaneous:

Miscellaneous:


Insulation Resistance:

Voltage: Tolerance:

Features:

RoHS:

Capacitor, Film, Metallized Paper, 0.47 uF, +/-20% Tol, -40/+85C, Integrated Resistor (X2), 630 VDC@85C, Lead Spacing=25.4 mm, Not For New Design, Please Check Possible Alternative Parts (AltPart)



Dimensions (mm)			
Symbol	Dimension	Tolerance	
L	30.5	MAX	
Н	22	MAX	
Т	15.3	MAX	
S	25.4	+/-0.4	
LL	30	+5	
F	1	+/-0.05	

Packaging Specifications		
Package Kind:	Bulk	
Package Quantity:	75	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and	
we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the	
requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us	
with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.	

