



Product Description

Maximum reliability; Optimal strain relief; Large, variable clamping ranges; For cable diameters up to 98 mm



Application range

- In areas with high demands on special mechanical and chemical stability.
- Chemical industry
- Measurement and control technology
- Machine and apparatus construction
- Plant engineering

Benefits

- Maximum reliability
- Optimal strain relief
- Large, variable clamping ranges
- For cable diameters up to 98 mm

Design

- Metric connection thread acc. to EN 50262

Note

- Counter nut to be used SKINDICHT® SM-M
- For suitable accessories see SKINTOP® metric accessories



Technical Data

Caution

Installation dimensions and tightening torques see Appendix T21

Approvals

IP 69 K approval for sizes M75x1,5 to M110x2 pending UL, CSA, DNV, VDE approval for size M90x2 to M110x2 pending

Material

Body: Nickel plated brass Insert: Polyamide Seal: CR O-ring: NBR

Degree of protection

IP 68

IP 69 K

Range of temperature

-30°C up to +100°C

Article List

Part number	Part designation / size	Clamping range ØF mm	SW mm	Overall length C mm	Thread length D mm	Pieces / PU
SKINTOP® MS-M/SKINTOP® MSR-M						
53112000	12 x 1,5	3-7	16	26,5	6.5	100
53112010	16 x 1,5	4,5-10	20	32.0	7.0	100
53112020	20 x 1,5	7-13	24	35,5	8.0	50
53112030	25 x 1,5	9-17	29	37,5	8.0	25
53112040	32 x 1,5	11-21	36	42,2	9.0	25
53112050	40 x 1,5	19-28	45	49,5	9.0	10
53112060	50 x 1,5	27-35	54	52.0	10.0	5
53112070	63 x 1,5	34-45	67	61,3	15.0	5
53112080	63 x 1,5 plus	44-55	75	65,5	15.0	5
53112510	75 x 1,5	58-68	95	105.0	15.0	1
53112512	90 x 2	66-78	115	136.0	20.0	1
53112514	110 x 2	86-98	135	154.0	25.0	1

Footnote:

Photographs are not to scale and do not represent detailed images of the respective products.