Amphenol

METAL SHELL TYPE



Features:

- Miniature version of the standard XLR series.
- Diecast or Precision machined metal housings.
- Metal cable clamp supports cables from 2mm to 3.5mm (0.078" to 0.137")
- Precision machined pin contacts.
- Stamped socket contacts
- Solder cup or Printed Circuit board contacts
- Available in 3, 4, 5 or 6 contacts
- Postive latchlock
- Flexible cable grommet

PRODUCT - FIGURE	DRAWING	Dimensions in mm (inches)	DESCRIPTION	VARIATIONS	PART NUMBER
			Male cable connector, Machined contacts,	3 pole	AG3M
	ø10.5 [.413"]⇒		Nickel Finish	4 pole	AG4M
	<u> </u>	-52 [2.055"]		5 pole	AG5M
				6 pole	AG6M
	40.5 [1.596"]		Female cable connector, Stamped contacts, Nickel Finish	3 pole	AG3F
				4 pole	AG4F
		INICKELLIHISTI	5 pole	AG5F	
	49 [1.910"]		6 pole	AG6F	
	1.0 [.039*] 1.4 [.055*] 1.4 [.055*] 2.5 [.079*] 2.0 [.079*] 3 pole		Male chassis connector, Machined contacts, Nickel Finish	3 pole	AG3MCC
				4 pole	AG4MCC
				5 pole	AG5MCC
				6 pole	AG6MCC
	18.8 [.740*] 5.7 [.224*] 1.7 [.067*] 1.7 [Female chassis connector, Stamped contacts, Nickel Finish	3 pole	AG3FCRV
		14.0 [.551 ⁻]		4 pole	AG4FCRV
		210		5 pole	AG5FCRV
	11,4 [,449"]	-16.2 [.638"]		6 pole	AG6FCRV

